



- Gelato showcase with ventilated refrigeration available in 3 sizes.
- Automatic defrosting feature.
- One piece structure with ecological polyurethane insulation (HCFC & HFC free) with 60 mm thickness and 43 Kg/m<sup>3</sup>.
- Electronic control board and digital thermometer.
- Double glazed tempered glass with built in resistance for high humidity condensation.
- Tilt-down front access with glazed glass up to 45° angle for easy routine maintenance and cleaning procedure.
- High energy saving with sliding rear Plexiglass doors.
- Interior LED light illumination.

Features	Auro 12 G	Auro 18 G	Auro 24 G
Dimension <b>mm</b>	1235 x 1025 x 1175	1775 x 1205 x 1175	2280 x 1205 x 1175
Pan Capacity <b>Lt</b>	12 x 5 lt - 8 x 7 lt	18 x 5 lt - 12 x 7 lt	24 x 5 lt - 16 x 7 lt
Power Consumption (Standard) <b>W</b>	1650 W	2400 W	3150 W
Power Consumption (Defrost) <b>W</b>	2530 W	3700 W	4960 W
Refrigerant	R404a	R404a	R404a
Operation Temperature <b>°C</b>	-18 / -22 °C	-18 / -22 °C	-18 / -22 °C
Power Supply	220 V / 1 Ph / 50 Hz	220 V / 1 Ph / 50 Hz	220 V / 1 Ph / 50 Hz
Compressor Type	Hermetic	Hermetic	Hermetic
Defrost	Automatic + Manuel	Automatic + Manuel	Automatic + Manuel
Defrost Type	Hot Gas	Hot Gas	Hot Gas

